





YOUR ONE-STOP SHOP FOR EXPRESS LANE SERVICE



To Order Call 1-855-298-2687, visit MoparEssentialTools.com or contact your local MSE representative





Express Lane Overview

MOPAR® Express Lane was developed to help dealers retain more oil change business, as well as sell additional maintenance and repair services. Express Lane strengthens the whole dealership, attracting oil change customers who can become loyal maintenance and repair customers, and ultimately, loyal new-vehicle customers.

Mopar Service Equipment (MSE) can provide your dealership with a support team to determine your Express Lane tool and equipment needs. MSE has an industry-leading field sales organization and customer service center to provide assistance on product selection, application, service and support for a "One-Stop Shop!"

Leasing Programs to Meet Your Needs

We offer Competitive Rates! Please call for quote.

- 24, 36, 48, 60 or 72 month terms available
- First and last month payments due in advance (zero down/deferred payments available)
- \$1 end of lease purchase option
- \$5,000 minimum
- Personal Guarantee not required for most transactions
- Financing available to qualified business customers; subject to credit approval
- Document Fee Applies

Contact Mopar Service Equipment 1-855-298-2687

For Pricing or to place an Order Call 1-855-298-2687, visit MoparEssentialTools.com or contact your local MSE representative

REMINDER LABEL

PETFKGX00105 Slip-N-Grip® Service Reminder **Printer**

The FK-GX001-05 service reminder label system ensures a professional image and helps promote repeat business. It's intuitive LCD operation panel makes it easy to operate. Preprogrammed with 24 industry standard messages and will be programmed with your shop name and desired phone number to print on the bottom of each label.

NOTE: Please specify at time of ordering your shop/dealer name (maximum of 20 characters/spaces) and phone number as you would like it to appear at the bottom of each label.

Includes:

- Flexible keyboard that is spill resistant and can be wiped clean of any shop soils.
- 1 printer ribbon.

WARRANTY: 3 year limited warranty on the entire system.

Accessorv:

Printer ribbon (each)







Call 1-855-298-2687





VERTICAL CABINET / BATTERY TESTER





Vertical Express Lane Cabinet

12 gauge all-welded 031-02005JA express lane cabinet with swing doors.

Doors extend out sideways at 180°. This cabinet has 1 full width shelf on top. Below this shelf is a vertical partition with 8 half-width shelves on each side (four shelves each side). Includes full length label holders mounted on shelves. Labels for recommended initial stocking levels also included.

MUST BE ANCHORED TO FLOOR.

Features:

- · Self-adhesive label holders each shelf level.
- · Labels representing stock numbers of initial recommended items.
- · Includes 2" peg hooks for windshield wipers.
- Included cups to hang on pegboard for light bulbs.
- Cabinet front labled with MOPAR® and Magnetti Marelli logos.
- Dimensions: 48" I x 18" w x 78" h includes 4" tall legs.





MTRED18V3MOP ED-18v3 MOPAR® Battery Tester

"Why test? It looks fine to me." — "It started to get me here."

In the real world, nobody cares about their battery — until it fails. Then, customers purchase to solve the problem, side-stepping your service lane for a specialty store, or in many cases, purchasing directly from the roadside service vehicle. With the MOPAR® ED-18 tester, the guesswork is removed and you are in a position to preserve the security and satisfaction of your customers — demonstrating genuine care:

You help to prevent "car-down/won't start" situations that hurt survey results and negatively affect customer relationships.



Dynamic Conductance Battery Testing Technology

Onboard VIN Barcode scanner for faster test speeds.

NOTE: The MTRED18V3MOP does generate a Chrysler warranty code.

- · Onboard Wi-Fi radio.
- Battery and System test functionality.
- Improved heavy-duty clamps and cables.
- Durable design with rubber protective boot.
- Built-in printer.

- "10 Steps to Testing" sales aid.
- · Summary of Dealer best practices.
- Communicating Battery Test Results sales aid.
- Easy operation and screen flow.
- Improved battery temperature reading with laser aiming feature.
- · Easy software updating through Wi-Fi connectivity.
- AGM Compliant.

4 Adivi Compilan



Call 1-855-298-2687





TOOL CART AND HAND TOOLS

MCOJSC500LEK

Matco Express Lane Cart and Complete
Tool Kit with Express Lane logo plate*

Features:

- JSC500-LA-MELKIT Matco Express Lane Cart stores over 60 tools (tools included, see page 3 for complete list).
- Heavy-Duty Service Cart built to withstand the harshest work environments so your investment will serve you well for many years to come.
- Durable bumper system protects vehicles and other objects around the shop.
- Lid accessory has a new built-in pry bar/screwdriver rack for added convenience.
- Unibody Case Construction the fully-welded Center Shelf and Interior Vertical Wall tie the structure of the box together and ensure the Matco toolbox is square, sturdy and stable.
- Structural Corner Posts the 16-gauge steel posts have multiple 90° angles to increase the load-bearing capacity of the Matco toolbox.
- Double-Wall Construction each double-wall of the Matco toolbox is internally reinforced with vertical L-channels to increase the load capacity and rigidity of the box to ensure it never cracks or distorts over time.
- Drawer Construction the drawers and slides are fully-integrated into the toolbox case design. An added channel support and over 20 bends in the steel of each drawer make each strong, durable and rigid.
- Upgraded side handle for easy maneuvering.
- For added protection, Service Cart, Lid Accessory and Drawer Accessories come with a nice top mat.
- Four (4) swivel casters and Matco's high security locking system.

Specifications:

- Roller bearing slide load capacity: 140 lbs. per pair
- Caster size: 6" x 2"
- Caster load capacity: 600 lbs.
- Dimensions: 42.3" h x 36" w x 24.5" d
- Total storage capacity: 13,678 cubic inches
- Lockable capacity: 11,449 cubic inches
- Color: Yellow
- Estimated weight for cart: 225 lbs. empty
- Complete Tool Kit weight: Estimated 135 lbs.

*Express Lane logo plate available for Enrolled MOPAR® Express Lane dealers only. Call 1-855-298-2687 for other available options.

† Free freight offer only valid within the United States including AK and HI. Does not apply to MCOTGMBLLA 682-TGMBLLA Matco Tech Series Gloves.

NOTE: Please allow 4 weeks for delivery.



ontact Mopar Program Headquar at 800-356-3490 for details.



Also Available:

MCOJSC500LAE JSC500-LA-MEL Matco Tools Service Cart

Only with Lid and Express Lane logo plate*

MCOJSC450LAK JSC450-LA-KIT Matco Tools Economical

Three Drawer Service Cart with Lid and

Express Lane logo plate*

MCOJSC450LAM JSC450-LA-MEL Matco Tools Economical

Three Drawer Service Cart Only with Lid and

Express Lane logo plate*

MCOMELTOOLKI MEL-TOOLKIT Complete Tool Kit Only, Matco.

See page 3 for a full list of the tool kit

MCOTGMBLLA TGMBLLA Matco Tech Series Gloves.

(See page 13 for details)

Call 1-855-298-2687





HAND TOOLS



THE MOST COMPLETE OIL CHANGE TOOL KIT OFFERING TO SERVICE ALL MAKES AND MODELS

MCOMELTOOLKI Complete Matco Tool Kit Includes the Following Items:

Item	Part Number	Qty.	Description
1	MC088850	1	Matco LED Penlight
2	MC090102US	1	2-1/2" Quick Change Chuck
3	MC093007MX	1	#2 Phillips Power Bit X 2"
4	MC093025MX	1	#2 Phillips Power Bit X 2-1/2"
5	MC093067MX	1	#2 Phillips Power Bit X 6"
6	MC093761MX	1	1/4" Socket Adaptor
7	MC093784MX	1	3/8" Socket Adaptor
8	MCOA101A	1	Dual Foot Inflator
9	МСОНКМ8	1	8 mm Allen Wrench
10	MCOBFR118TG	1	3/8" Drive Ratchet — Matco Handle 88
11	MCOBG842	1	Brake Gauge — Color Coded
12	MCOBSATX7A	1	1/4" Drive 7-Piece Torx Quick Bits
13	MCOBX24KA	1	3/8" Drive 24" Extension
14	MCOBX6WKA	1	3/8" Drive Wobble Extension 6"
15	MC0BXYS10M	1	3/8" Drive Stubby 10 mm Hex Socket
16	MCOBXYS8M	1	3/8" Drive Stubby 8 mm Hex Socket
17	MCOCFR158TG	1	1/2" Drive Ratchet — Matco Handle 88
18	MC0FS75031	1	Center Cap Removal Tool
19	MCOCXP3B	1	3" Impact Extension 1/2" Drive
20	MCOCXY14M	1	1/2" Drive 14 mm Hex Socket
21	MCODB45	1	45 oz. Dead Blow Hammer
22	MC0EIVM614	1	3/8" Drive 14 mm Stubby Hex Socket
23	MCOG201	1	Safety Goggles
24	MCOGG45	1	Pistol Grip Grease Gun
25	MCOGGA21600	1	Right Angle Grease Gun Adaptor
26	MCOLSC4487	1	Hood Clamps
27	MCOLT1240	1	Lugnut Socket 21/21.5 mm
28	MCOLT1250	1	Lugnut Socket 18.5/19.5 mm
29	MCOLT1260	1	Lugnut Socket 22/22.5 mm
30	MCOMC24M2A	1	24 mm Wrench
31	MCOMKHS	1	Matco Kevlar Heat Sleeve
32	MCOMSG10	1	10' X 1/2" Touch Release Tape Measure
33	MCOMST60A	1	3-Jaw Oil Filter Wrench

FREE Freight Included!†

em	Part Number	Qty.	Description
34	MCOMT2769	1	1/2" Composite Air Impact Wrench
35	MCOMTTDG	1	Metal Tire Depth Gauge
36	MCOMUC122IW	1	12 Volt Cordless Drill
37	MCOOFSHD10	1	10-Piece Oil Filter Wrench Set
38	MCOOF5075A	1	Oil Filter Pliers
39	MC00F5095	1	Oil Filter Pliers
40	MC00F571	1	No-Slip Oil Filter Wrench
41	MC00F572	1	No-Slip Oil Filter Wrench
42	MC00F573	1	No-Slip Oil Filter Wrench
43	MCOOF574	1	No-Slip Oil Filter Wrench
44	MC00F632	1	Oil Filter Wrench — Adjustable
45	MCOOF636	1	Oil Filter Wrench — Adjustable
46	MCOOFS6906	1	Toyota Tundra Oil Filter Tools — 5.7L and 4.7L
47	MCOOFSR6024	1	Oil Filter — 3/8" Square Drive 24 mm
48	MCOOFSR6032	1	3/8" Square Drive 32 mm Oil Filter Socket
49	MCOOFSR6027	1	3/8" Drive 27 mm Oil Filter Housing Socket
50	MCOPU3SA	1	3-Piece Pliers Set — PBDC8, PNC8, PC10
51	MCOSAM106TB	1	1/4" Drive 10-Piece Socket Set 5 mm – 14 mm
52	MCOSBDM146TA	1	14-Piece 3/8" Deep Metric Sockets 6-Point
53	MCOSBLXK3TB	1	3-Piece 3/8" Drive Locking Extension Set
54	MCOSBM126TA	1	12-Piece 3/8" Drive Metric Sockets 6-Point
55	MCOSCC3	1	Anti-Freeze Hydrometer
56	MCOSCM156TA	1	15-Piece 1/2" Drive Metric Sockets
57	MCOSCXK5TA	1	5-Piece 1/2" Drive Extension Set
58	MCOSF198	1	Super Funnel
59	MCOSG375MLC	1	Safe Grip Microflex Gloves/Case
60	MCOSMCL92T	1	9-Piece SAE Long Combo Wrench Set 3/8"
61	MCOSMCLM122T	1	12-Piece Metric Long Combo Wrench Set
62	MCOSSPC05C	1	5-Piece Screwdrivers — Slotted/Phillips
63	MCOSTTF56P	1	5-Piece Wheel Lug Flip-Socket Set
64	MCOTRC250A	1	1/2" Drive Torque Wrench
35	MCOTT32	1	Rubber Mallet
66	MCOWSPP2	1	Wheel Stud Installer, 12m x 1.25

Please allow 4 weeks for delivery.

† Free freight offer only valid within the United States including AK and HI. Does not apply to MCOWTK1510WR MSE Torque Socket Set.

Also Available:

MCOMCL18IWVS

MCL18IWVSKIT Cordless Impact (battery operated; includes charger, battery and carrying case)

NOTE: MSE Torque Sticks not included in Matco Tool Kit. Please order MCOWTK1510WR separately through MSE.

MCOWTK1510WR

Torque Socket Set, 10-Piece. (See page 12 for details)

Call 1-855-298-2687





HIGH SPEED LIFTS

Challenger Lifts

DX77 Double Scissor Lifts Recommended Lift for MOPAR_® Express Lane.

Features:


- The hydraulically synchronized system provides 7,700 lbs. lifting capacity.
- Double scissor has 74" rise height allowing more overall working clearance.
- Faster rise time of 43 seconds providing optimum performance for express service.
- Platform has reinforced diamond plated ramps which easily flip up to extend platform for longer wheelbase vehicles such as trucks or vans.
- Mechanical safety lock with air actuated release allows technician to work at an ergonomic height to increase productivity and minimize fatigue.
- Simple operation power unit console has three push-button controls for: Raise, Lower and Lock Release.
- Can be installed flush-mounted or floor-mounted.

Benefits:

 Express Lanes can benefit from speed spotting, drive through capabilities and the ability for technicians to easily and quickly reach the area needing service.

Specifications:


Models	CLFDX77	CLFDX77R
Lifting capacity*	7,700 lb. (3493 kg)	7,700 lb. (3493 kg)
Installation	Standard	Flush-Mount
Rise height	74-1/2" (1890 mm)	70" (1775 mm)
Overall length (Lowered)	82-3/4" (2102 mm)	82-3/4" (2102 mm)
Overall length (Raised)	83-1/4" (2114 mm)	83-1/4" (2114 mm)
Overall width	79-3/4" (2026 mm)	68-1/4" (1733 mm)
Platform length	59" (1500 mm)	59" (1500 mm)
Platform width	23-1/2" (600 mm)	23-1/2" (600 mm)
Width between platforms**	21" (533 mm)	21" (533 mm)
Ramp length	11-3/4" (300 mm)	11-3/4" (300 mm)
Lowered height	4-1/2" (116 mm)	- 11-11-1
Motor	3 hp, 1-phase, 60 Hz	3 hp, 1-phase, 60 Hz
Voltage	208/230 volt	208/230 volt
Air supply required	90 – 120 p.s.i.	90 – 120 p.s.i.
Speed of rise	43 Seconds	43 Seconds
Maximum load per platform	3,850 lbs. (1746 kg)	3,850 lbs. (1746 kg)



** Width between platforms is based on hose and hose guard length. Measurements are done from floor to top of platform.

NOTE: Shipping and handling charge of 3.5% will be added to all Challenger orders.





Provided 60" (standard length) air and hydraulic hoses allow three ergonomic, recommended power console placement options.



Power unit console houses three simple button push controls: Raise, Lower and Lock Release.

Call 1-855-298-2687





HIGH SPEED LIFTS

Snap-on Equipment

SOET9000 9,000 Lb. Double XL Automotive/ General-Purpose Scissor Lift

Features:

- Lifts straight up 5.3" low 79.75" high.
- Open front and rear with no cross-member for maximum accessibility.
- Dual hydraulic synchronization.
- · 18 mechanical locking positions with air-actuated release.
- Non-slip textured lifting pad surface.
- Extendible lifting pad, from 61.25" 81.5".
- Above-ground installation requires the optional SOET9000LW Outrigger-Ramp Kit and Runways added to allow installation at 23" apart.
- Surface-Mount or Flush-Mount configurations.
- ALI/ETL/CSA certified.

Specifications:

- Lifting capacity: 9,000 lbs.
- Surface-mounted maximum raised height: 79.75"
- Lifting time: 53 seconds (with full load)
- Lift pad length: 61.25"
- Lift pad width: 25.5"
- Overall width: 86.875" maximum
- Surface-Mount lowered height: 5.3"
- Air supply requirement: 90 p.s.i.
- Power requirements: 230 volts, 1 phase, 60 Hz
- 208/230 volt, 60 Hz, 3 phase
- Shipping weight: 2,700 lbs



Accessories:

SOET9000LW Outriggers and low-profile approach ramps (required for above-ground installations)

SOE-VZ970052 Hydraulic Hose Extension Kit (required for flush-mount installations)

SOE-VZ970133 Insert Plates (required for flush-mount installations)

SOE-VZ970045 Plastic Chocks (4 piece)

SOE-VZ975074 Connector Rubber Blocks (set of 4)

NOTE: The **SOET9000LW** is required for above-ground installation to allow the lift to be installed at the recommended Chrysler vehicle application width of 23" between runways. The **SOE-VZ970052** Hydraulic Hose Extension Kit and **SOE-VZ970133** Insert Plates are required for flush-mount installations.

Call 1-855-298-2687





HIGH SPEED LIFTS



ROTSPOA10RAS 10,000 Lb. SHOCKWAVE™ Two-Post Lift

SPOA10-RA-SW Shockwave™ Equipped Rotary Lifts will help you achieve your goals of greater technician productivity and higher profits. Designed for fast-service bays . . . Only available from Rotary.

Features:

- Two times faster up and down than most lifts on the market.
- Battery power reduces energy use, has built-in charger and operates on 110 volt vs. 220 volt. Batteries not included.
- Spotline™ laser allows vehicles to be spotted in center of bay on first try.

Specifications:

- Rise*: 73-7/8" (1876 mm)
- Height overall**: 11' 8-1/2" (3569 mm)
- Width overall**: 11' 5-1/2" (3493 mm)
- Drive-thru clearance: 95-1/4" (2416 mm)
- Floor-to-overhead switch: 11' 2-3/4" (3423 mm)
- Reach (front arm minimum): 21-5/8" (550 mm)
- Reach (front arm maximum): 43-1/2" (1106 mm)
- Reach (rear arm minimum): 34-1/2" (878 mm)
- Reach (rear arm maximum): 58" (1474 mm)
 Minimum adaptor height: 3-5/8" (93 mm)
- High step height: 5-7/8" (149 mm)
- Cylinder height (full rise)*: 12' 4-3/4" (3778 mm)/ 11' 10-3/4" (3626 mm)
- Lifting capacity: 10,000 lbs. (4536 kg)
- Motor: 2 hp
- Voltage single phaset: 208 230 volt
- Time of full rise: 45 seconds
- Ceiling height required: 12' (3658 mm)
- Maximum load per arm: 2,500 lbs. (1134 kg)
- **Minimum bay size:** 12' x 24' (3658 x 7315 mm)
- * Rise is measured to top of adaptor in highest position with lift at full rise.
- ** Overall heights and widths reflect standard settings. Alternate settings may be available. Refer to product installation instructions or consult your equipment representative.
- † Optional 3 phase electrical available.

Standard color of lift is blue. Red is available upon request.

NOTE: All orders are subject to a 3.75% shipping and handling fee.









OIL DRAINS



GRC239-301 16 Gallon Receiver with Drum

Features:

- · Caster base.
- Drum cover with front level gauge.
- · Funnel assembly.
- · 16 gallon drum.



GRC238-866 Oil King 25 Gallon Used Oil Receiver

Includes:

- · Polyethylene tank with used filter tray.
- · Tool holders.
- 4" capped port and site gauge.
- All hardware for top side evacuation or bottom drain.

For technical information call 1-248-647-1159.



SAMSON

SMN373400 18 Gallon Air Evacuation Oil Drain

Features:

- Eliminates the need for a separate pumping system.
- Shop air is used with 6-1/2' discharge hose.
- · Conveniently portable.
- Unit has built-in safety valve to prevent over pressurization of tank.
- · All metal construction.
- · Heavy-duty 5 gallon collection bowl.



Balcrank

BCK4110-010 Spillguard Maximum-Duty Drain

Features:

- 19-1/4" telescoping bowl extends to 65" height.
- Quick height adjustment.
- Wide track dolly.
- 16 gallon drum, dipstick, bowl screen and drum spigot.
- Drum level float indicator and dry-break hydraulic evacuation nipple mounted above the drum.



Call 1-855-298-2687





FLUID DISPENSING AND STORAGE



Bulk Fluid Dispensing Packages

Features:

- Cubet containers are ULC Listed C142.14.
- Tank is made of high density polyethylene material that meets NSF 51 requirements and FDA specifications.
- · Space-saving only 34" of floor space.
- No drum handling or deposits.
- No vent cap needed.
- Support stand keeps tank 4" 5" off the floor.
- · Fluid level always visible, no gauge needed.
- · Will not leak or rust.
- Package shipped assembled.

Models:

\$\$03232 230 Gallon Cubet

SMN3216 140 Gallon Cubet



Bulk Fluid Storage

Features:

- Leak-proof and will not corrode
- Outer tank holds 110% of inner tank for maximum protection
- Up to 50% lighter than conventional steel tanks
- · Can use for heating oil, diesel and bio fuels, motor oil, DEF, and ATF
- Compact economical design
- · Provides maximum storage safety with minimum space requirements
- Removable base facilitates access to tight spaces and greater stability
- Wide handles on each end allow you to transport and handle with ease
- Quality control and testing exceeds industry standards
- Certified to UL2258

Models:

RTH335109001 110 Gallon Double-Wall Oil/Fuel Storage Tank

RTH335109002 165 Gallon Double-Wall Oil/Fuel Storage Tank

RTH335109003 275 Gallon Double-Wall Oil/Fuel Storage Tank

RTH335109005 400 Gallon Double-Wall Oil/Fuel Storage Tank



Call 1-855-298-2687





FLUID DISPENSERS



SDP5 Electronic Preset Metered Dispense Valves

Models:

GRC255200 Rigid extension. US measure
GRC255351 Flexible extension. US measure
GRC255352 Offset extension. US measure



SAMSON

Ergonomically Designed Metered Fluid Handles

Specifications:

Models	Fluid Application	Outlet	Meter Units of Measure
SMN1144	ATF, mechanical	Flex hose	Quart
SMN1140	Gear oil, mechanical	Rigid elbow	Pint
SMN1172	Motor oils, mechanical	Rigid	Quart
SMN2161	Oil, electronic	Rigid	Quart
SMN2165	ATF, electronic	Flex hose	Quart



Balcrank

BCK3330159 DR (Digital Registry) Metered Control Handle

Simple, Accurate and Efficient! The DR meter is precision balanced, lightweight and ergonomically designed.

Features:

- Memory-flex extension; bend the extension to the desired angle and it retains shape.
- No field calibration required.
- Measures quarts, pints, gallons and liters.
- Unique 1/4 turn manual tip: effective and very fast, high flow, no splash and very easy to use.
- Swivel cover protects automobiles from nicks and scratches.
- Affordable repairability: Electronic Register Module (ECR) can be changed easily.









HOSE REELS

Balcrank

BCK2120-020 Open Air/Water Hose Reels

50' x 1/2".

Features:

- Low pressure hose reels.
- Wide beam structural parts.
- 8-position locking precision die cast latch.
- Machined thick wall hub parts.
- · Heavy-gauge stamped rims.
- 5-position outlet arm and wide 6-roller outlet.

Also Available:

BCK2120-014 30' x 3/8" **BCK2120015** 50' x 3/8"





GRCHPM65B Heavy-Duty SD20 Series Open Hose Reel

Features:

- · Unique base-mount hose guide for tank mounting.
- · Lightweight, slotted base for easy installation.
- Factory installed fluid hose stays flexible for easier handling, even under pressure.
- · Multi-position hose guide for overhead applications.
- Air hose 1/2" x 50'.

Also Available:

GRCHPL56B Air and Water 3/8" x 65' hose, 1,800 p.s.i.

GRCHPH15B Grease 1/4" x 50' hose, 1,800 p.s.i.

GRCHPH55B Grease 3/8" x 50' hose, 1,800 p.s.i.

GRCHPM65B Oil Grease 1/2" x 50' hose, 2,000 p.s.i.



Call 1-855-298-2687





REEL LIGHTS/DRAIN PLUG/BRAKE PAD GAUGE



WTT36135004 50' STUBBY II® Automatic Fluorescent Reel Light

Features:

- Lite-n-lok micro switch on/off, no external switches.
- Conforms to UL standard 355 for use above hazardous locations.
- Provides same light as 75 100 watt incandescent.
- Patented rough service lamp.
- Cord: 50', 18/2 SJTOW wire.
- . Bulb: 13 watt dual-filament fluorescent.
- · Made in the USA.

WTT19408000 40' Stubby II[®] LED Reel Light

Features:

- Stubby II LED with end light, 40' reel.
- Models are available with or without flashlight end.
- · Single switch in handle controls all LEDs.
- Long Life LEDs are rated to 50,000 hours and equivalent to 13 watt fluorescent.
- One watt high output LED provides a bright flashlight out the end.
- Quality anodized heat sink prevents LEDs from overheating.
- Soft bumpers provide impact protection to the fixture.





OTC5911 Drain Plug Pro™

Hot Oil in the Pan — Not on your Hand!

Features:

- Remove oil drain plug without touching the plug or hot oil.
- NO touching HOT plug.
- NO HOT oil on hands.
- NO dropping of plug in HOT oil.
- NO oil soaked gloves.
- Just magnetically attach DRAIN PLUG PRO[™] to pre-loosened drain plug and rotate to remove plug.





Brake Pad Gauge

Features:

- The 6596 Brake Pad Gauge allows for a definitive measurement of brake pads to determine remaining life.
- Unique design allows for measurement on the vehicle without the removal of any components in most cases (wheel assembly or brake caliper).
- Quick reference of brake pad condition via color code scale.

Barrel Measurement	Quick Reference Color	Brake Pad Condition
8 mm or more	Green	No replacement necessary
3 mm to 8 mm	Yellow	Suggest replacement soon
0 mm to 3 mm	Red	Recommend replacement

Call 1-855-298-2687





TORQUE SOCKETS/HOOD PROP/HUBCAP REMOVER



MCOWTK1510WR 10 Piece Torque Socket Set with Wall Rack

Features:

- · Handles most passenger car and light truck applications
- Use with 1/2" drive pneumatic impact wrench
- These special 1/2" drive torque sockets avoids over-torque of wheel nuts and prevents damage
- · Includes ten sockets and a convenient wall rack

WARRANTY: Lifetime





WTT46170 Hood Prop with Support

Features:

- · Includes a support to help prevent slipping.
- 3-piece telescoping shaft locks in any position to hold hood to the desired height.
- Tool with the support telescopes from 20" 48-1/4".
- Place the support over hood adjuster.
- · Set the hood prop base into the holding support.





WTTT68 Ken Tool Hubcap Remover/Installer

Features:

Use to remove and install hubcaps.



Call 1-855-298-2687





GLOVES AND HOT SLEEVE

WTT6501004 Solution Solution



Features:

- · Powder-free latex.
- 8 mil.
- Exam grade.
- Textured surface for gripping power.
- · Easy slip-on comfort.
- · Protein rated.
- · Beaded cuff.
- · 100 gloves by weight per box.



MCOTGMBLLA Tech Series Gloves



Features:

- Clarino® synthetic leather with an exclusive single-piece palm design.
- 40 mm wide elastic woven cuff with ergonomic Velcro[®] closure tab.
- · Double-stitched seams in all the critical strength areas.
- · Reinforced thumb, wrist and fingertip wear-guards.
- · Machine washable.
- · Size: Large. Color: Blue

NOTE: Other sizes and colors available at MoparEssentialTools.com.



WTT18700 Hot Sleeve

Features:

- Protects arms from burns while working around the engine.
- Made of durable, heat-resistant Kevlar[®].
- Double wall construction for added heat protection.
- Will protect hand and forearm from hot objects.
- Will work on either right or left arm.
- Sleeve is washable.



Call 1-855-298-2687



P.O. Box 1450 Kenosha, WI 53141



For Pricing or to place an Order Call 1-855-298-2687, visit MoparEssentialTools.com or contact your local MSE representative



Pricing is for Alfa Romeo, Chrysler, Dodge, Fiat®, Jeep $_{\odot}$ and RAM dealers only. Pricing is noted in US Dollars. Pricing and product information are subject to change without notice.

All sales F.O.B. shipping point. All applicable freight, installation and tax will be added at time of invoice. For estimated freight, please call 1-855-298-2687.